QT Series



QT50L / QT50ML
QT70L / QT70ML

New Model Concept which Allows for Significant Customization to Your Specific Needs Using Special Modular Components



· QT Series tower light is a multifunctional product that allows for significant customization to your specific needs using our special modular components such as the lens, buzzer, USB cord and Mounting brackets. Additional tools are not required for assembly
· All modular components can be arranged freely to the user desired position (upper/ lower) except for the dial tone lever



· **Buzzer modules position can be chosen freely**
The buzzer module is designed to be compatible with the light modules by using a novel architecture developed by Qlight. Therefore, users can reposition the module to the location they desire. In the photo to the left, the buzzer module is located at the top, center and bottom positions.



· **Can select from a variety of LED light functions**
The LED indicator can provide varying signals/actions by using different independent light modules; flashing, strobe, rotating. For example, green would indicate normal operation, a red module would indicate risk which can be highlighted further by selecting a strobe flashing or rotating module.



1 Buzzer Tone Type
1 Buzzer Tone Type

· **Buzzer sound selection**
Modules that output buzzer sounds can be arranged according to the work environment and purpose.
For detailed specifications of the buzzer sound module, please refer to QT Series [Buzzer Module].



· **Can select from a variety of pole selections to fit your application needs**
You can choose from 8 different kinds of pole options for mounting. The pole materials vary from steel, aluminum, and polycarbonate. Please refer to [Tower Light Mounting Bracket] on this catalogue for detailed dimensions




· **Module sales**
Consumers can purchase the modules they need and assemble them themselves.
Detailed specifications and features of the module are introduced on the QT50 / QT70 module information page.
References for module combinations are included on the Assembly Instructions page.

· **Assembly sales**
We assemble the functions requested by consumers and supply them as finished products.
Assembly specifications for various model numbers are introduced on the QT50 / QT70 product detail page.

QT Series

Multi-functional module can be assemble to user requirements



Please use the switch for Steady and Flashing which is on top of Q50L-F and Q70L-F, LED steady/flashing module.

Module Connection




1 Connect wire between module



2 Match the edge of module



3 To assemble turn right



Uses a connector for easy assembly

LED module

· 4 kinds of LED modules; Steady, steady/flashing, strobe, revolving flashing
· Good visibility with high brightness.
· Module position can be chosen based on signal importance.



Q70L-N



Q50L-N

LED Steady Module
· Output LED Steady signal
· High brightness LED
· Voltage: DC12V, DC24V, AC110V, AC220V



Q70L-F



Q50L-F

LED Steady/Flashing Module
· Output LED Steady/Flashing signal
· High brightness LED
· Voltage: DC12V, DC24V, AC110V, AC220V



Q70L-S



Q50L-S

LED Strobe Module
· LED Strobe Module
· Excellent notice compare to flashing type
· Voltage: DC12V, DC24V



Q70L-R



Q50L-R

LED Revolving Flashing Module
· LED light revolve and flash
· Dynamic Signal
· Voltage: DC12V, DC24V

Buzzer module

· Buzzer module has Siren and Bip sound, Bip sound is adjustable.
· Buzzer module position can be chosen freely and has a good air tight seal.



Q70L-BZS

Siren Sound Buzzer Module
· Siren buzzer volume: Max.90dB
· Sound fixed
· Voltage: DC12V, DC24V, AC110V, AC220V




Q70L-BZ



Q50L-BZ

Bip Sound Buzzer Module
· Bip sound(Pi-Pi) volume : Max 90dB
· Sound adjustable
· Voltage: DC12V, DC24V, AC110V, AC220V



· Sound adjustable by lever on module side
· Buzzer module position can be chosen freely

Module Connection

· Adopts a convenient connector for easy assemble.
· Simple connection structure makes assembly straightforward and effortless when compared to other manufacturer's products.


Base Module is composed of the control line and threaded to the Mounting bracket for improved product mounting efficiency.
Please refer to below instruction and choose the mount type.



QT70L-BS QT50L-BS

Base Module

· 6P terminal plate equipped on basic module. Please refer to QT Series wiring diagram for wiring of power line and signal line

Direct mount		3 Bolts on base module
Wall mount		Wall mount bracket on base module
Pole mount		Pole module and pole assemble on base module

Module Color

· Housing color of the QT series modular tower lights is black
· Customizable in beige color

Wiring Instructions

· QT series can be wired to External Contact and transistor
· In case of wiring with transistor, please select the proper transistor type either NPN or PNP based on the source voltage setting
· External power/External signal line - UL1007 AWG22(0.3sq) 400mm


Mounting bracket

· Pole Mount Brackets

Standard	LB18 LB24	LW18 LW24	QZ18 QZ24	SZ18 SZ24	QL18 QL24	SL18 SL24	SLB370
							
Steel	Steel	ABS	ABS	Al	ABS	Al	PC, Steel

※ Please refer to [Tower Light Mounting bracket] on this catalogue for detailed dimensions

Power Line Wiring Instructions




Terminal box can be wired without a special tool by using the push and release locking mechanism.

QT70 Series


Module Specifications QT70L / QT70ML

(Units : mm)

Appearance	Parts Name	Model No	Common Specifications
	QT70L Cover	Q70L-CV	· Material: PC · Protection ratings with assemble: IP65 · Product size: Ø70 x 15 


· LED Steady Module

(Units : mm)

Appearance	Parts Name	Model No	Specifications		Common Specifications
			Voltage	Current	
	Q70L-NR Red LED Steady Module	Q70L-NR-12 Q70L-NR-24 Q70L-NR-110 Q70L-NR-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	· Material: PC · Protection ratings with assemble : IP65 · Product size: Ø70 x 65 
	Q70L-NA Amber LED Steady Module	Q70L-NA-12 Q70L-NA-24 Q70L-NA-110 Q70L-NA-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	
	Q70L-NG Green LED Steady Module	Q70L-NG-12 Q70L-NG-24 Q70L-NG-110 Q70L-NG-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	
	Q70L-NB Blue LED Steady Module	Q70L-NB-12 Q70L-NB-24 Q70L-NB-110 Q70L-NB-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	
	Q70L-NC White LED Steady Module	Q70L-NC-12 Q70L-NC-24 Q70L-NC-110 Q70L-NC-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	

· LED Flashing Module


(Units : mm)

Appearance	Parts Name	Model No	Specifications		Common Specifications
			Voltage	Current	
	Q70L-FR Red LED Steady/Flashing Module	Q70L-FR-12 Q70L-FR-24 Q70L-FR-110 Q70L-FR-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	· Material: PC · Protection ratings with assemble : IP65 · Product size: Ø70 x 65 
	Q70L-FA Amber LED Steady/Flashing Module	Q70L-FA-12 Q70L-FA-24 Q70L-FA-110 Q70L-FA-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	
	Q70L-FG Green LED Steady/Flashing Module	Q70L-FG-12 Q70L-FG-24 Q70L-FG-110 Q70L-FG-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	

QT70 Series

(Units : mm)


Appearance	Parts Name	Model No	Specifications		Common Specifications
			Voltage	Current	
	Q70L-FB Blue LED Steady/Flashing Module	Q70L-FB-12 Q70L-FB-24 Q70L-FB-110 Q70L-FB-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	· Material: PC · Protection ratings with assemble: IP65 · Product size: Ø70 x 65
	Q70L-FC White LED Steady/Flashing Module	Q70L-FC-12 Q70L-FC-24 Q70L-FC-110 Q70L-FC-220	DC12V DC24V AC110V AC220V	120mA 55mA 25mA 25mA	



· LED Strobe Module

(Units : mm)


Appearance	Parts Name	Model No	Specifications		Common Specifications
			Voltage	Current	
	Q70L-SR Red LED Strobe Module	Q70L-SR-12 Q70L-SR-24	DC12V DC24V	120mA 120mA	
	Q70L-SA Amber LED Strobe Module	Q70L-SA-12 Q70L-SA-24	DC12V DC24V	120mA 120mA	
	Q70L-SG Green LED Strobe Module	Q70L-SG-12 Q70L-SG-24	DC12V DC24V	120mA 120mA	· Material: PC · Protection ratings with assemble: IP65 · Product size: Ø70 x 65
	Q70L-SB Blue LED Strobe Module	Q70L-SB-12 Q70L-SB-24	DC12V DC24V	120mA 120mA	
	Q70L-SC White LED Strobe Module	Q70L-SC-12 Q70L-SC-24	DC12V DC24V	120mA 120mA	




· LED Revolving Flashing module

(Units : mm)

Appearance	Parts Name	Model No	Specifications		Common Specifications
			Voltage	Current	
	Q70L-RR Red LED Revolving Flashing Module	Q70L-RR-12 Q70L-RR-24	DC12V DC24V	80mA 80mA	· Material: PC · Protection ratings with assemble: IP65 · Product size: Ø70 x 65
	Q70L-RA Amber LED Revolving Flashing Module	Q70L-RA-12 Q70L-RA-24	DC12V DC24V	80mA 80mA	




(Units : mm)

Appearance	Parts Name	Model No	Specifications		Common Specifications
			Voltage	Current	
	Q70L-RG Green LED Revolving Flashing Module	Q70L-RG-12 Q70L-RG-24	DC12V DC24V	80mA 80mA	· Material: PC · Protection ratings with assemble: IP65 · Product size: Ø70 x 65
	Q70L-RB Blue LED Revolving Flashing Module	Q70L-RB-12 Q70L-RB-24	DC12V DC24V	80mA 80mA	
	Q70L-RC White LED Revolving Flashing Module	Q70L-RC-12 Q70L-RC-24	DC12V DC24V	80mA 80mA	

· Buzzer module

(Units : mm)


Appearance	Parts Name	Model No	Specifications		Common Specifications
			Voltage	Current	
	Q70L-BZ Buzzer module	Q70L-BZ-12 Q70L-BZ-24 Q70L-BZ-110 Q70L-BZ-220	DC12V DC24V AC110V AC220V	30mA 55mA 110mA 130mA	· Material: PC · Protection ratings with assemble: IP54 · Product size: Ø70 x 65 · Volume: Max.90dB
	Q70L-BZS Siren Buzzer module	Q70L-BZS-12 Q70L-BZS-24 Q70L-BZS-110 Q70L-BZS-220	DC12V DC24V AC110V AC220V	240mA 150mA 10mA 20mA	

QT70 Series

· Base Module







(Units : mm)

Appearance	Parts Name	Model No	Common Specifications
	Base Module	Q70L-BS Q70L-MBS	· Material: PC · Protection ratings with assemble: IP65 · Product size: Ø70 x 36



· Mount Bracket Module

(Units : mm)

Appearance	Parts Name	Model No	Material	Technical Diagram
	Wall Mount Bracket	TWS80	Steel	 
	Wall Mount Bracket	TWA80	PC	 
	Pole Module	Q70L-PB	PC	 

QT70ML

IP65 | +50℃ -30℃ | NPN | PNP

Product consist of cover, LED modules, signal sound module, base module

QT70ML Ø70mm Direct Mount Modular LED Tower Lights

Model number	Layers	Voltage	Certificates	Weight	Color
QT70ML QT70MLF	1	DC12V DC24V AC110V AC220V	CE	0.17kg 0.17kg 0.18kg 0.18kg	R-Red
	2	DC12V DC24V AC110V AC220V		0.25kg 0.25kg 0.26kg 0.26kg	R-Red G-Green
	3	DC12V DC24V AC110V AC220V		0.32kg 0.32kg 0.33kg 0.33kg	R-Red A-Amber G-Green
	4	DC12V DC24V AC110V AC220V		0.40kg 0.40kg 0.41kg 0.41kg	R-Red A-Amber G-Green B-Blue
	5	DC12V DC24V AC110V AC220V		0.47kg 0.47kg 0.48kg 0.48kg	R-Red A-Amber G-Green B-Blue W-White

※ CE compliant: DC12V, DC24V



QT70ML

Beige color

Beige color is available



module configuration

QT70ML QT70MLF	Steady Module Steady/Flashing Module	+	Base Module(MBS)

Light source current(based on 1 layer)

Voltage	DC12V	DC24V	AC110V	AC220V
Light source current(1 layer)	120mA	55mA	25mA	25mA

Wiring Instructions

· LED tower light can be wired by using transistor and external contact

Customization

· Beige color
· LED Strobe(Model number: QT70MLS)
· LED simulated revolving(Model number: QT70MLR)
· Wall mount bracket options : Bracket structure allows for threading through the bracket hole or into the wall



Wall mount bracket TWS80




Wall mount bracket TWA80

Technical Diagram

Units : mm

·QT70ML



LAYER	L
1	98
2	154
3	210
4	266
5	322

Ordering Specification

QT70ML	-	3	-	220	-	RAG

[Model number]	[Layers]	[Voltage]	[Color]
QT70ML QT70MLF	1-1 Layer 2-2 Layers 3-3 Layers 4-4 Layers 5-5 Layers	12-DC12V 24-DC24V 110-AC110V 220-AC220V	R-Red A-Amber G-Green B-Blue W-White

QT70ML-BZ

IP54 | +50°C -30°C | BUZZER | 90dB | NPN | PNP

Product consist of cover, LED modules, buzzer module, base module



QT70ML-BZ

Beige color
Beige color is available



QT70ML-BZ Ø70mm Direct Mount Modular LED Tower Lights with Buzzer

Model number	Layers	Voltage	Certificates	Weight	Color
QT70ML-BZ QT70MLF-BZ (Max. 90dB)	1	DC12V DC24V AC110V AC220V	CE	0.26kg 0.26kg 0.27kg 0.27kg	R-Red
	2	DC12V DC24V AC110V AC220V		0.34kg 0.34kg 0.35kg 0.35kg	R-Red G-Green
	3	DC12V DC24V AC110V AC220V		0.42kg 0.42kg 0.43kg 0.43kg	R-Red A-Amber G-Green
	4	DC12V DC24V AC110V AC220V		0.49kg 0.49kg 0.50kg 0.50kg	R-Red A-Amber G-Green B-Blue

※ CE compliant: DC12V, DC24V

module configuration

QT70ML QT70MLF	Steady Module Steady/Flashing Module	+	Base Module(MBS)	+	Buzzer module(BZ)


Light source/buzzer current(based on 1 layer)

Voltage	DC12V	DC24V	AC110V	AC220V
Light source current(1 layer)	120mA	55mA	25mA	25mA
Buzzer current	30mA	55mA	110mA	130mA

Technical Diagram

Units : mm

·QT70ML-BZ



LAYER	L
1	154
2	210
3	266
4	322

Wiring Instructions

· LED tower light can be wired by using transistor and External Contact

Customization

· Beige color
· LED Strobe(Model number : QT70MLS-BZ)
· LED simulated revolving (Model number: QT70MLR-BZ)
· Wall mount bracket options : Bracket structure allows for threading through the bracket hole or into the wall



Wall mount bracket TWS80



Wall mount bracket TWA80

Ordering Specification



QT70ML-BZ	-	3	-	220	-	RAG
[Model number]		[Layers]		[Voltage]		[Color]
QT70ML-BZ QT70MLF-BZ		1-1 Layer 2-2 Layers 3-3 Layers 4-4 Layers		12-DC12V 24-DC24V 110-AC110V 220-AC220V		R-Red A-Amber G-Green B-Blue

QT Series

Wiring Instructions(Wiring using External Contact)





· QT Series can be wired by using both External Contact and transistor.

· In case of wiring with External Contacts, refer to the wiring diagrams below according to your product's type and voltage setting.

	Wiring instructions		Wiring instructions
DC/AC standard		DC/AC buzzer	
QT50ML(F) QT50MLS(DC only) QT50MLR(DC only) QT50L(F) QT50LS(DC only) QT50LR(DC only) QT70ML(F) QT70MLS(DC only) QT70MLR(DC only) QT70L(F) QT70LS(DC only) QT70LR(DC only)		QT50ML(F)-BZ QT50MLS-BZ(DC only) QT50MLR-BZ(DC only) QT50L(F)-BZ QT50LS-BZ(DC only) QT50LR-BZ(DC only) QT70ML(F)-BZ QT70MLS-BZ(DC only) QT70MLR-BZ(DC only) QT70L(F)-BZ QT70LS-BZ(DC only) QT70LR-BZ(DC only)	

Wiring Instructions(Wiring using transistor)

· In case of wiring by transistor, please make sure if it is NPN type or PNP type. Please carefully follow wiring instruction below.

	Wiring instructions	
DC standard		
QT50ML(F) QT50MLS QT50MLR QT50L(F) QT50LS QT50LR QT70ML(F) QT70MLS QT70MLR QT70L(F) QT70LS QT70LR		
DC buzzer		
QT50ML(F)-BZ QT50MLS-BZ QT50MLR-BZ QT50L(F)-BZ QT50LS-BZ QT50LR-BZ QT70ML(F)-BZ QT70MLS-BZ QT70MLR-BZ QT70L(F)-BZ QT70LS-BZ QT70LR-BZ		

· External power/External signal line - UL1007 AWG22(0.3sq) 400mm