QTG-IOL Series


PRODUCT SPECIFICATION

QTG60L-IOL | QTG70L-IOL

Materials Housing-ABS, Lens-PC
Ambient operating temperature 30°C to +50°C
Sound volume High-volume buzzer Max.100dB at 1m
Waterproof buzzer Max.85dB at 1m
Protection rating
Standard/Waterproof Buzzer-IP65
High-Volume Buzzer-Non-Waterproof



- Modular LED steady/flashing type signal tower lights
- Excellent visibility from a distance with the use of a special color diffusing lens
- Can select from size selections of Ø60mm and Ø70mm to fit your sophisticated application needs
- The addition of modules and change in color arrangement can be achieved without the use of tools by using the Lock-type structure
- Advanced LED signal tower light integrated with IO-Link technology
- Ideal for next-generation smart manufacturing systems (Industry 4.0)
- Plug & Play functionality enabled by international standard M12 connector
- IO-Link Version: V1.1
- Data transmission speed: 38,400 bps (COM2)
- Connector: M12-5Pin(Male)-Class A



Each modular color lens can be added without additional tools



QTG model uses a special contact structure for stable operation, the lens modules lock into place by rotating the modular structures together. This allows for easy changes to the color arrangement without any tools. Additional modules can be added.

1. **High volume buzzer(100dB) option can be fitted to the top of the product**
High volume 100dB volume buzzer module fastened to the top of the product provides 360 degree buzzer signal output which cannot be achieved with the single directional buzzer.(Buzzer volume cannot be adjusted.)

2. **Waterproof buzzer (85dB) option can be fitted to the top of the product**
Waterproof 85dB buzzer module fastened to the top of the product features an IP65-rated sealed structure and offers improved sound dispersion compared to conventional front-directional buzzers.

3. **Excellent visibility from a distance with the use of a special color diffusing lens**
Color arrangement changes and module additions can be easily made without the use of tools by adopting a lock-type structure between lenses.


4. **M12 connector attached type**
The application of the IO-Link standard M12 connector allows for convenient installation and maintenance.

IP65 | +50℃ -30℃ | BUZZER | 85dB | 100dB | RoHS2

QTG60L-IOL Ø60mm IO-Link Programmable LED Tower Light

Model number	Layers	Voltage	Certificates	Weight	Color
QTG60L-IOL Steady/Flashing	1	DC24V	IO-Link, CE, UL	0.25kg	R-Red
	2			0.33kg	R-Red G-Green
QTG60L-IOL-HBZ Steady/Flashing w/ built-in high volume buzzer	3			0.41kg	R-Red A-Amber G-Green
QTG60L-IOL-WBZ Steady/Flashing w/ built-in waterproof buzzer	4			0.49kg	R-Red A-Amber G-Green B-Blue
	5			0.57kg	R-Red A-Amber G-Green B-Blue W-White

※ Simultaneous use of the white color LED module with high volume buzzer (HBZ) or waterproof buzzer (WBZ) is not supported.




QTG60L-IOL

QTG70L-IOL Ø70mm IO-Link Programmable LED Tower Light

Model number	Layers	Voltage	Certificates	Weight	Color
QTG70L-IOL Steady/Flashing	1	DC24V	IO-Link, CE, UL	0.37kg	R-Red
	2			0.52kg	R-Red G-Green
QTG70L-IOL-HBZ Steady/Flashing w/ built-in high volume buzzer	3			0.67kg	R-Red A-Amber G-Green
QTG70L-IOL-WBZ Steady/Flashing w/ built-in waterproof buzzer	4			0.82kg	R-Red A-Amber G-Green B-Blue
	5			0.97kg	R-Red A-Amber G-Green B-Blue W-White

※ Simultaneous use of the white color LED module with high volume buzzer (HBZ) or waterproof buzzer (WBZ) is not supported.



QTG70L-IOL

Light source/buzzer current of QTG60L-IOL and QTG70L-IOL (based on 1 layer)

Voltage	Light source current (1 layer)	High volume buzzer current	Waterproof buzzer current
DC24V	70mA	90mA	90mA

Ordering Specification

QTG60L-IOL	-	3	-	24	-	RAG	-	LB32
[Model number]		[Layer]		[Voltage]		[Color]		[Bracket]
QTG60L-IOL QTG60L-IOL-HBZ QTG60L-IOL-WBZ QTG70L-IOL QTG70L-IOL-HBZ QTG70L-IOL-WBZ		1-1Layer 2-2Layers 3-3Layers 4-4Layers 5-5Layers(Excluding HBZ, WBZ)		24-DC24V		R-Red A-Amber G-Green B-Blue W-White		· None -Standard · Bracket -LB32

Bracket

· It can be installed on the wall by adopting wall mounting type bracket.




Wall mount bracket
LB32

QTG-IOL Series


Technical Diagram

Units: mm


·QTG60L-IOL



·QTG60L-IOL-HBZ




·QTG60L-IOL-WBZ




LAYER	L1	L2	L3
1	175	213	212
2	225	263	262
3	275	313	312
4	325	363	362
5	375	-	-


·QTG70L-IOL



·QTG70L-IOL-HBZ



·QTG70L-IOL-WBZ




LAYER	L1	L2	L3
1	175	213	212
2	225	263	262
3	275	313	312
4	325	363	362
5	375	-	-

Wiring Instructions

· Please follow the IO-Link M12 wiring standard.

M12 connector PIN-MAP

QTG60L-IOL
QTG70L-IOL



PIN	DESCRIPTION
1	Brown(L+)
2	White(NC)
3	Light Blue(L-)
4	Black(C/Q)
5	Gray(NC)