Metal cylindrical shape capacitive sensors **CQ32G**series



Features

- ◆ Be able to detect both metal and nonmetal objects;
- ◆ Be able to detect various media via nonmetallic container;
- ◆ Reliable liquid level detecting;


Part number

AC2 wires	NO	CQ32GCF15ATO	AC2 wires	NC	CQ32GCF15ATC

Technical specifications

Mounting	Flush	Leakage current [Ir]	≤3mA
Rated distance [Sn]	15mm (adjustable)	Circuit protection	… …
Assured distance [Sa]	0…12mm	Output indicator	Yellow LED
Dimensions	Φ32*80mm	Ambient temperature	-25℃…70℃
Output	NO/NC(depends on part number)	Ambient humidity	35-95%RH
Supply voltage	20…250 VAC	Switching frequency [F]	15 Hz
Standard target	Fe45*45*1t	Voltage withstand	2000V/AC 50/60Hz 60S
Switch-point drifts [%/Sr]	≤±20%	Insulation resistance	≥50MΩ (500VDC)
Hysteresis range [%/Sr]	3…20%	Vibration resistance	10…50Hz (1.5mm)
Repeat accuracy [R]	≤3%	Degree of protection	IP67
Load current	≤300mA	Housing material	Stainless steel
Residual voltage	≤10V	Connection type	2m PVC cable

Dimensions



Wiring diagram

