Plastic square shape inductive sensors **LE36** series



Features

◆Non contact detection, safe and reliable;
◆ASIC design;
◆Perfect choice for metallic targets detection;

CE


Part number

NPN	NO	LE36SF05DNO	LE36SN08DNO	PNP	NO	LE36SF05DPO	LE36SN08DPO
NPN	NC	LE36SF05DNC	LE36SN08DNC	PNP	NC	LE36SF05DPC	LE36SN08DPC

Technical specifications

Mounting	Flush	Non-flush	Current consumption	≤10mA	
Rated distance [Sn]	5mm	8mm	Circuit protection	Short-circuit, overload and reverse polarity	
Assured distance [Sa]	0…4mm	0…6.4mm	Output indicator	Yellow LED	
Dimensions	8 *36 *60 mm		Ambient temperature	-25℃…70℃	
Output	NO/NC(depends on part number)		Ambient humidity	35-95%RH	
Supply voltage	10…30 VDC		Switching frequency [F]	700 Hz	500Hz
Standard target	Fe 36*36*1t	Fe 36*36*1t	Voltage withstand	1000V/AC 50/60Hz 60s	
Switch-point drifts [%/Sr]	⩽±10%		Insulation resistance	≥50MΩ(500VDC)	
Hysteresis range [%/Sr]	1…20%		Vibration resistance	10…50Hz (1.5mm)	
Repeat accuracy [R]	⩽3%		Degree of protection	IP67	
Load current	⩽200mA		Housing material	PBT	
Residual voltage	⩽2.5V		Connection type	2m PVC cable	

Dimensions



Wiring diagram

