NAMUR inductive sensors **LE40SZ** series



Features

- ◆ Non-contact detection, safe and reliable;
- ◆ Low voltage and current output, suitable for explosive area;

CE


Part number

NAMUR	LE40SZSF15FLCN-E2	LE40SZSN20FLCN-E2


Technical specifications

Mounting	Flush	Non-flush	Load resistance	⩾1KΩ	
Rated distance [Sn]	15mm	20mm	Circuit protection	…	
Assured distance [Sa]	0…12mm	0…16mm	Output indicator	…	
Dimensions	40*40*66 mm		Ambient temperature	-25℃…70℃	
Output	NAMUR		Ambient humidity	35…95%RH	
Supply voltage	8.2 VDC		Switching frequency [F]	400 Hz	250 Hz
Standard target	Fe 45*45*1t	Fe 60*60*1t	Voltage withstand	…	
Switch-point drifts [%/Sr]	⩽±10%		Insulation resistance	≥50MΩ (500VDC)	
Hysteresis range [%/Sr]	1…20%		Vibration resistance	10…50Hz (1.5mm)	
Repeat accuracy [R]	⩽3%		Degree of protection	IP67	
Output current	Triggered ⩽1mA		Housing material	PBT	
	Not triggered ⩾2.2mA		Connection type	M12 connector	

Dimensions



Wiring diagram



NAMUR

