NAMUR inductive sensors **LR08** series



Features

- Non-contact detection, safe and reliable;
- Low voltage and current output, suitable for explosive area;

CE


Part number

NAMUR	LR08AF15FLCN	LR08AN02FLCN


Technical specifications

Mounting	Flush	Non-flush	Load resistance	⩾1KΩ	
Rated distance [Sn]	1.5mm	2mm	Circuit protection	…	
Assured distance [Sa]	0…1.2mm	0…1.6mm	Output indicator	…	
Dimensions	M8*22mm	M8*25mm	Ambient temperature	-25℃…70℃	
Output	NAMUR		Ambient humidity	35…95%RH	
Supply voltage	8.2 VDC		Switching frequency [F]	2500 Hz	2000Hz
Standard target	Fe 8*8*1t	Fe 8*8*1t	Voltage withstand	…	
Switch-point drifts [%/Sr]	⩽±10%		Insulation resistance	≥50MΩ (500VDC)	
Hysteresis range [%/Sr]	1…20%		Vibration resistance	10…50Hz (1.5mm)	
Repeat accuracy [R]	⩽3%		Degree of protection	IP67	
Output current	Triggered ⩽1mA		Housing material	Stainless steel SUS 303	
	Not triggered ⩾2.2mA		Connection type	2m PVC cable	

Dimensions



Wiring diagram



NAMUR