Plastic square shape photoelectric sensors **PTF** series



Features

- ◆Through beam reflection working principle;
- ◆Excellent anti-interference performance
- ◆High detection accuracy


Part number

		Emitter	Receiver			Emitter	Receiver
NPN	NO	PTF-TM20D	PTF-TM20DNO	PNP	NO	PTF-TM20D	PTF-TM20DPO
NPN	NC	PTF-TM20D	PTF-TM20DNC	PNP	NC	PTF-TM20D	PTF-TM20DPC
NPN	NO+NC	PTF-TM20D	PTF-TM20DNR	PNP	NO/NC	PTF-TM20D	PTF-TM20DPR


Technical specifications

Detection type	Through beam	Consumption current	≤25mA
Rated distance [Sn]	20m (non-adjustable)	Circuit protection	Short-circuit and reverse polarity
Standard target	＞φ15mm opaque object	Response time	＜8.2ms
Light source	Infrared LED (880nm)	Output indicator	Emitter: Green LED Receiver: Yellow LED
Dimensions	50 mm *50 mm *17mm	Ambient temperature	-15℃…+55℃
Output	NO/NC (depends on part No.)	Ambient humidity	35-85%RH (non-condensing)
Supply voltage	10…30 VDC	Voltage withstand	1000V/AC 50/60Hz 60s
Min target	……	Insulation resistance	≥50MΩ(500VDC)
Hysteresis range [%/Sr]	……	Vibration resistance	10…50Hz (0.5mm)
Repeat accuracy [R]	≤5%	Degree of protection	IP64
Load current	≤200mA (receiver)	Housing material	PC/ABS
Residual voltage	≤2.5V (receiver)	Connection type	2m PVC cable

Dimensions




Emitter




Receiver


Wiring diagram




Emitter




NPN NO




PNP NO




NPN NC



PNP NC



NPN NO+NC



PNP NO+NC