Metal cylindrical shape photoelectric sensors **PR18G** series



Features

- ◆Retro reflection working principle;
- ◆Excellent anti-interference performance
- ◆High detection accuracy


Part number

AC 2 wires	NO	PR18G-DM3ATO	AC 2 wires	NC	PR18G-DM3ATC

Technical specifications

Detection type	Retro reflection	Consumption current	≤3mA
Rated distance [Sn]	3m (non-adjustable)	Circuit protection	……
Standard target	TD-09 reflector	Response time	< 50ms
Light source	Infrared LED (880nm)	Output indicator	Yellow LED
Dimensions	M18*83.5mm	Ambient temperature	-15℃…+55℃
Output	NO/NC (depends on part No.)	Ambient humidity	35-85%RH (non-condensing)
Supply voltage	20…250 VAC	Voltage withstand	2000V/AC 50/60Hz 60s
Target	Opaque object	Insulation resistance	≥50MΩ(500VDC)
Hysteresis range [%/Sr]	……	Vibration resistance	10…50Hz (0.5mm)
Repeat accuracy [R]	⩽5%	Degree of protection	IP65
Load current	⩽300mA	Housing material	Nickel-copper alloy
Residual voltage	⩽10V	Connection type	2m PVC cable

Dimensions



Wiring diagram

