
Miniature photoelectric sensor **PSV** series



Feature description

- Small size, easy to install and use
- With 360° visible bright LED status indicator
- Superior anti-light interference, stable product performance
- Red light source for easy adjustment and alignment

CE

Model specification


NPN NO	PSV-YR15DNOR	PNP NO	PSV-YR15DPOR
NPN NC	PSV-YR15DNCR	PNP NC	PSV-YR15DPCR

Specifications

Detection distance	15mm①	Indicator	Green:power,stable indicator;Yellow:output indicator
Dead zone	<2mm	Response time	<1ms
Standard test body	50*50mm white cards	Anti ambient light	Sunlight interference ≤10,000 lux
Light spot size	2mm@30mm		Incandescent light interference ≤3,000 lux
Color sensitivity	> 90%	Operating temperature	-20...55 ºC
Hysteresis	< 20%	Storage temperature	-30...70 ºC
Supply voltage	10...30V DC	Protection degree	IP65
Consumption current	≤15mA	Certification	CE
Load current	≤50mA	Shell material	PC+PBT
Voltage drop	< 1.5V	Lens	PC
Light source	Red light(680nm)	Weight	22g
Protection circuit	Short circuit protection,Polarity protection	Connection	2m PVC cable
	Overload protection,Zener protection	Accessory	Screws(M2×8mm)×2、Nut×2


①Use 50*50mm white card with reflectivity greater than 90%

Dimension




* Lanbao reserves all the rights

Wiring diagram



NPN



PNP

* Lanbao reserves all the rights