Ultrasonic sensor **UR30-CM4** series



Feature Description

- M30 installation threaded sleeve
- Extended long distance detection
- 1 NPN or PNP switch output
- Analog voltage output 0-5/10V or analog current output 4-20mA
- Digital TTL output
- Output can be changed through serial port upgrade
- Setting detection distance through teach-in lines
- Temperature compensation

CE UKCA


Model specifications

NPN	NO/NC	UR30-CM4DNB	PNP	NO/NC	UR30-CM4DPB
NPN	Hysteresis mode	UR30-CM4DNH	PNP	Hysteresis mode	UR30-CM4DPH
0-5V	Analog output	UR30-CM4DU5	4-20mA	Analog output	UR30-CM4DI
0-10V	Aanalog output	UR30-CM4DU10	Com	TTL232	UR30-CM4DT


Specifications

Sensing range	200-4000mm	Output indication	Red LED: No target detected in teach-in state, always on
Blind area	0-200mm		Yellow LED: In normal working mode, the switch status
Resolution ratio	1mm		Blue LED: Target detected in teach-in state, flashing
Repeat accuracy	±0.15% of full scale value		Green LED: Power indicator light, always on
Absolute accuracy	±1% (temperature drift compensation)	Input type	With teach-in function
Response time	300ms	Ambient temperature	-25℃…70℃(248-343K)
Switch hysteresis	2mm	Storage temperature	-40℃…85℃(233-358K)
Switching frequency	3Hz	Output characteristics	Support serial port upgrade and change the output type
Power on delay	＜500ms	Material	Copper nickel plating, glass bead filled epoxy resin
Working voltage	9...30VDC	Protection degree	IP67
No-load current	≤25mA	Connection	2m PVC cable


Dimension




Wiring diagram



NPN Output



Analog Output



PNP Output



TTL232