



Servet

CATALOG

**SERVET
AGRICULTURAL
MACHINES**

2
0
2
3



TECHNICAL SPECIFICATIONS				
PRODUCT DESCRIPTION				
LOADING TONNAGE	1 TON	1.5 TON	2 TON	
BRAND NAME	SERVET	SERVET	SERVET	SRVT01SABT
PRODUCT CODE	SRVT01SABT	SRVT15SABT	SRVT20SABT	SRVT30SABT
ALLOWABLE TOTAL WEIGHT	1650kg	2320kg	2800kg	3500kg
LOADING CAPACITY	1000kg	1500kg	2000kg	2500kg
LOADING CAPACITY (Wheat 1Ton=1,0416m ³)	1430kg	2023kg	2700kg	3360kg
EMPTY WEIGHT	650kg	820kg	1000kg	1220kg
LOAD VOLUME	1,49m ³	2,1m ³	2,7m ³	3,3m ³
LOADING SPACE	2,70m ²	3,8m ²	4,9m ²	6,0m ²
LOADING CASE INSIDE LENGHT	2220mm	2520mm	2820mm	3120mm
LOADING CASE INSIDE WIDTH	1220mm	1520mm	1820mm	2120mm
DIMENSIONS; LENGHT/WIDTH/HEIGHT	2300/1300/300-250mm	2600/1600/300-250mm	2900/1900/300-250mm	3200/2200/300-250mm
TOTAL LENGHT/WIDTH/YÜKSEKLİK	3360/1380/1400mm	3750/1680/1450mm	4140/1980/1500mm	4530/2280/1550mm
PLARFORM HEIGHT MEASURED FROM FLOOR	670mm	670mm	670mm	670mm
SIDEWALL HEIGHT	300mm	300mm	300mm	300mm
FLOOR THICKNESS (mm)	2,5mm	2,5mm	2,5mm	2,5mm
WALL THICKNESS (mm)	2mm	2mm	2mm	2mm
WHEEL TRACK	1420mm	1420mm	1420mm	1420mm
SUSPENSION	Optional	Optional	Optional	Optional
TYRES	Optional	Optional	Optional	Optional
MAXIMUM SPEED	20km	20km	20km	20km
TIPPING SYSTEM	Optional	Optional	Optional	Optional
TELESCOPIC CYLINDER (Piston Stage/Oil Required/Working Pressure)	2 Stage / 7,1 lt/160 bar	2 Stage/7,1 lt/160 bar	2 Stage/7,1 lt/160 bar	2 Stage/7,1 lt/160 bar
BRAKE TYPE	Optional	Optional	Optional	Optional
CHASSIS	80NPU	80NPU	80NPU	80NPU
MINIMUM TRACTOR POWER REQUIREMENT	25Hp	35HP	45HP	55HP
TIPPING ANGLE (Backwards/Sides)	40/30	40/30	40/30	40/30
OPTIONALS				
TIPPING SYSTEM	BACK TIPPING - THREE SIDES TIPPING			
BRAKE TYPE	HYDRAULIC BRAKE / PNEUMATIC BRAKE			
SUSPENSION	LEAF SPRING / PARABOLIC			
TYRES	185/70	650/16	750/16	
	6,50/16	600*16	10/80-12	
	600/16	10/80-12		
	7,50/16			
TOP & BOTTOM OPENABLE LIDS	✓	✓		
REAR BRAKE OUTPUT	✓	✓		
REAR DAMPER OIL OUTLET	✓	✓		
REAR TOWBAR	✓	✓		
WHEEL JACK	✓	✓		
HYDRAULIC JACK	✓	✓		
EXTRA ADDITIONAL	✓	✓		
HEAVY COVER	✓	✓		
LADER	✓	✓		
PLASTIC TOOL CABINET	✓	✓		
PLASTIC WATER TANK	✓	✓		
SPARE TYRE	✓	✓		

**SERVET
AGRICULTURAL
MACHINES**

[illegible]

SINGLE AXLE BACK TI



TECHNICAL SPECIFICATIONS	
PRODUCT DESCRIPTION	
LOADING TONNAGE	4T
BRAND NAME	SERVET
PRODUCT CODE	SRVT40SABTDW
ALLOWABLE TOTAL WEIGHT	5550kg
LOADING CAPACITY	4000kg
LOADING CAPACITY (Wheat 1Ton=1,0416m3)	4675kg
EMPTY WEIGHT	1550kg
LOAD VOLUME	4,87m3
LOADING SPACE	6,50m2
LOADING CASE INSIDE LENGHT	3220mm
LOADING CASE INSIDE WIDTH	2020mm
DIMENSIONS; LENGHT/WIDTH/HEIGHT	3300/2100/450-300mm
TOTAL LENGHT/WIDTH/YÜKSEKLİK	4650/2200/1720mm
PLARFORM HEIGHT MEASURED FROM FLOOR	1030mm
SIDEWALL HEIGHT	450mm
FLOOR THICKNESS (mm)	3mm
WALL THICKNESS (mm)	2,5mm
WHEEL TRACK	1600mm
SUSPENSION	Optional
TYRES	Optional
MAXIMUM SPEED	40km
TIPPING SYSTEM	Optional
TELESCOPIC CYLINDER (Piston Stage/Oil Required/Working Pressure)	3 Stage/8 lt/160 bar
BRAKE TYPE	Optional
CHASSIS	140NPU
MINIMUM TRACTOR POWER REQUIREMENT	50Hp
TIPPING ANGLE (Backwards/Sides)	40/30
OPTIONALS	
TIPPING SYSTEM	BACK TIPPING - THREE SIDES TIPPING
BRAKE TYPE	HYDRAULIC BRAKE / PNEUMATIC
SUSPENSION	LEAF SPRING / PARABOLIC
	7,50/16*4-HUMMEL
TYRES	
TOP & BOTTOM OPENABLE LIDS	✓
REAR BRAKE OUTPUT	✓
REAR DAMPER OIL OUTLET	✓
REAR TOWBAR	✓
WHEEL JACK	✓
HYDRAULIC JACK	✓
EXTRA ADDITIONAL	✓
HEAVY COVER	✓
LADER	✓
PLASTIC TOOL CABINET	✓
PLASTIC WATER TANK	✓
SPARE TYRE	✓

PPING DOUBLE WHEEL

SERVET
AGRICULTURAL
MACHINES



SINGLE AXLE BACK TIPPING DOUBLE WHEEL			
	5T	6T	8T
	SERVET	SERVET	SERVET
	SRVT50SABTDW	SRVT60SABTDW	SRVT80SABTDW
	6600kg	7600kg	9950kg
	5000kg	6000kg	8000kg
	5300kg	6490kg	8776kg
	1600kg	1600kg	1950kg
	5,52m3	6,76m3	9,14m3
	6,90m2	7,51m2	8,31m2
	3420mm	3720mm	3920mm
	2020mm	2020mm	2120mm
	3500/2100/450-350mm	3800/2100/450-450mm	4000/2200/500-300-300mm
	4650/2200/1720mm	4900/2200/1760mm	5300/2300/2120mm
	1030mm	1030mm	
	450mm	450mm	500mm
	3mm	3mm	4mm
	2,5mm	2,5mm	2,5mm
	1600mm	1600mm	1600mm
	Optional	Optional	Optional
	Optional	Optional	Optional
	40km	40km	40km
	Optional	Optional	Optional
	3 Stage/8 lt/160 bar	3 Stage/12 lt/160 bar	3 Stage/12 lt/160 bar
	Optional	Optional	Optional
	140NPU	180NPU	180NPU
	50Hp	50Hp	50Hp
	40/30	40/30	40/30
PPING			
IC BRAKE			
	7,50/16*4-HUMMEL	7,50/16*4-HUMMEL	7,50/16*4-HUMMEL
			8.25/20*4-HUMMEL
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓

TO VIEW ON
THE WEBSITE





TECHNICAL SPECIFICATIONS				
PRODUCT DESCRIPTION				
LOADING TONNAGE	3T	4T	5T	6T
BRAND NAME	SERVET	SERVET	SERVET	SERVE
PRODUCT CODE	SRVT30DABT	SRVT40DABT	SRVT50DABT	SRVT60D
ALLOWABLE TOTAL WEIGHT	4240kg		6920kg	8250k
LOADING CAPACITY	3000kg	4000kg	5000kg	6000kg
LOADING CAPACITY (Wheat 1Ton=1,0416m3)	5,49kg	5779kg	8486kg	9149kg
EMPTY WEIGHT	1240kg	2000kg	1920kg	2250kg
LOAD VOLUME	5,27m3	6,02m3	9m3	9,53m
LOADING SPACE	7,03m2	7,53m2	8,48m2	9,53m
LOADING CASE INSIDE LENGHT	3620mm	3920MM	4420mm	4720m
LOADING CASE INSIDE WIDTH	1820mm	1920MM	1920mm	2020m
DIMENSIONS; LENGHT/WIDTH/HEIGHT	3700/1900/400-350mm	4000/2000/500-300mm	4500/2000/600-400mm	4800/2100/600
TOTAL LENGHT/WIDTH/YÜKSEKLİK	5250/2000/1850mm	5550/2100/1940mm	6250/2100/2000mm	6550/2200/2
PLARFORM HEIGHT MEASURED FROM FLOOR	1020mm	1150mm	1150mm	1150m
SIDEWALL HEIGHT	400mm	500MM	600mm	600mm
FLOOR THICKNESS (mm)	2,5mm	3mm	3mm	3mm
WALL THICKNESS (mm)	2mm	2mm	2,5mm	2,5mm
WHEEL TRACK	1530mm	1560mm	1600mm	1600mm
SUSPENSION	Optional	Optional	Optional	Option
TYRES	Optional	Optional	Optional	Option
MAXIMUM SPEED	40km	40km	40km	40km
TIPPING SYSTEM	Optional	Optional	Optional	Option
TELESCOPIC CYLINDER (Piston Stage/Oil Required/Working Pressure)	3 Stage/11 lt/160bar	3 Stage/11 lt/160 bar	4 Stage/8 lt/160 bar	4 Stage/8 lt/
BRAKE TYPE	Optional	Optional	Optional	Option
CHASSIS	140NPU	140NPU	140NPU	140NP
MINIMUM TRACTOR POWER REQUIREMENT	50HP	50HP	50HP	50HP
TIPPING ANGLE (Backwards/Sides)	40/30	40/30	40/30	40/30
OPTIONALS				
TIPPING SYSTEM	BACK TIPPING - THREE SIDES TIPPING			
BRAKE TYPE	HYDRAULIC BRAKE / PNEUMATIC BRAKE			
SUSPENSION	LEAF SPRING / PARABOLIC			
TYRES	6,50/16	750/16 1394	900/16 1985	900/16 1985
	7,50/16	900/16 1985	11.5/80-15.3 2464	11.5/80-15.3 246
		11.5/80-15.3 2464	400/60-15.5 3549	400/60-15.5 354
			12.5/80-15.3 5300	12.5/80-15.3 530
TOP & BOTTOM OPENABLE LIDS	✓	✓	✓	✓
REAR BRAKE OUTPUT	✓	✓	✓	✓
REAR DAMPER OIL OUTLET	✓	✓	✓	✓
REAR TOWBAR	✓	✓	✓	✓
WHEEL JACK	✓	✓	✓	✓
HYDRAULIC JACK	✓	✓	✓	✓
EXTRA ADDITIONAL	✓	✓	✓	✓
HEAVY COVER	✓	✓	✓	✓
LADER	✓	✓	✓	✓
PLASTIC TOOL CABINET	✓	✓	✓	✓
PLASTIC WATER TANK	✓	✓	✓	✓
SPARE TYRE	✓	✓	✓	✓

BACK TIPPING

SERVET
AGRICULTURAL
MACHINES

DOUBLE AXLE BACK TIPPING					
	8T	10T	12T	14T	16T
T	SERVET	SERVET	SERVET	SERVET	SERVET
ABT	SRVT60DABT	SRVT100DABT	SRVT120DABT	SRVT140DABT	SRVT160DABT
g	10500kg	12750kg	15000kg	17400KG	19800kg
g	8000kg	10000kg	12000kg	14000KG	16000kg
g	9600kg	10000kg	15725kg	16530KG	11789kg
g	2500kg	2750kg	3000kg	3400KG	3800kg
3	10m3	10,43m3	16,38m3	17,22m3	12,28m3
2	10m2	10,43m3	10,92m2	11,48m2	11,70m2
m	4720mm	4920mm	4920mm	5170mm	5270mm
m	2120mm	2120mm	2220mm	2220mm	2220mm
0-400mm	4800/2200/600-400mm	5000/2200/600-400mm	5000/2300/700-400-400mm	5250/2300/700-400-400mm	5350/2300/600-450mm
200mm	6750/2200/2550mm	6600/2300/2350mm	6980/2400/2800mm	6850/2400/2500mm	6900/2400/2500mm
m	1200mm	1280mm	1300mm	1300mm	
n	600mm	600mm	700mm	700MM	600mm
	3mm	3mm	3mm	3mm	3mm
n	2,5mm	2,5mm	2,5mm	2,5mm	2,5mm
m	1700mm	1700mm	1700mm	1700mm	1700mm
al	Optional	Optional	Optional	Optional	Optional
al	Optional	Optional	Optional	Optional	Optional
	40km	40km	40km	40km	40km
al	Optional	Optional	Optional	Optional	Optional
160 bar	4 Stage/20 lt/160 bar	4 Stage/20 lt/160 bar	4 Stage/20 lt/160 bar	4 Stage/20 lt/160 bar	4 Stage/20 lt/160 bar
al	Optional	Optional	Optional	Optional	Optional
U	160NPU	200NPU	200NPU	200NPU	200NPU
	50HP	50HP	50HP	50HP	50HP
	40/30	40/30	40/30	40/30	40/30
	400/60-15.5 3549	400/60-15.5 3549	400/60-15.5 3549	500/50-17.5 6186	385/65-22.5 7200
54	12.5/80-15.3 5300		500/50-17.5 6186	385/65-22.5 7200	435/50-19,5 9200
9				435/50-19,5 9200	
00					
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓
	✓	✓	✓	✓	✓

TO VIEW ON
THE WEBSITE





TECHNICAL SPECIFICATIONS			
PRODUCT DESCRIPTION			
LOADING TONNAGE	6T	8T	
BRAND NAME	SERVET	SERVET	
PRODUCT CODE	SRVT06TABT	SRVT08TABT	SRVT09TABT
ALLOWABLE TOTAL WEIGHT	8400kg	10600kg	12800kg
LOADING CAPACITY	6000kg	8000kg	10000kg
LOADING CAPACITY (Wheat 1Ton=1,0416m3)	10397kg	11693kg	13089kg
EMPTY WEIGHT	2400kg	2600kg	2800kg
LOAD VOLUME	10,83m3	12,18m3	13,53m3
LOADING SPACE	24,39m2	9,37m2	10,72m2
LOADING CASE INSIDE LENGHT	4220mm	4420mm	4620mm
LOADING CASE INSIDE WIDTH	2020mm	2120mm	2220mm
DIMENSIONS; LENGHT/WIDTH/HEIGHT	4300/2100/600-300-300mm	4500/2200/600-350-350mm	4500/2200/600-350-350mm
TOTAL LENGHT/WIDTH/YÜKSEKLİK	5450/2200/2350mm	5750/2300/2350mm	5750/2300/2350mm
PLARFORM HEIGHT MEASURED FROM FLOOR	1050mm	1050mm	1050mm
SIDEWALL HEIGHT	600mm	600mm	600mm
FLOOR THICKNESS (mm)	3mm	3mm	3mm
WALL THICKNESS (mm)	2,5mm	2,5mm	2,5mm
WHEEL TRACK	1700mm	1700mm	1700mm
SUSPENSION	Optional	Optional	Optional
TYRES	Optional	Optional	Optional
MAXIMUM SPEED	40km	40km	40km
TIPPING SYSTEM	Optional	Optional	Optional
TELESCOPIC CYLINDER (Piston Stage/Oil Required/Working Pressure)	4 Stage/10 lt/160 bar	4 Stage/10 lt/160 bar	4 Stage/10 lt/160 bar
BRAKE TYPE	Optional	Optional	Optional
CHASSIS	180NPU	180NPU	180NPU
MINIMUM TRACTOR POWER REQUIREMENT	55HP	55HP	55HP
TIPPING ANGLE (Backwards/Sides)	40/30	40/30	40/30
OPTIONALS			
TIPPING SYSTEM	BACK TIPPING - THREE SIDES TIPPING		
BRAKE TYPE	HYDRAULIC BRAKE / PNEUMATIC BRAKE		
SUSPENSION	LEAF SPRING / PARABOLIC		
	12.5/80-15.3	12.5/80-15.3	400/60-15.3
TYRES			12.5/80-15.3
TOP & BOTTOM OPENABLE LIDS	✓	✓	
REAR BRAKE OUTPUT	✓	✓	
REAR DAMPER OIL OUTLET	✓	✓	
REAR TOWBAR	✓	✓	
WHEEL JACK	✓	✓	
HYDRAULIC JACK	✓	✓	
EXTRA ADDITIONAL	✓	✓	
HEAVY COVER	✓	✓	
LADER	✓	✓	
PLASTIC TOOL CABINET	✓	✓	
PLASTIC WATER TANK	✓	✓	
SPARE TYRE	✓	✓	

BACK TIPPING

**SERVET
AGRICULTURAL
MACHINES**

[illegible]

TO VIEW ON
THE WEBSITE



SINGLE AXLE BACK



TECHNICAL SPECIFICATIONS	
PRODUCT DESCRIPTION	
LOADING TONNAGE	4T
BRAND NAME	SERVET
PRODUCT CODE	SRVT40SAB
ALLOWABLE TOTAL WEIGHT	5250kg
LOADING CAPACITY	4000kg
LOADING CAPACITY (Wheat 1Ton=1,0416m3)	3987kg
EMPTY WEIGHT	1050kg
LOAD VOLUME	4,15m3
LOADING SPACE	4,6m2
LOADING CASE INSIDE LENGHT	2652mm
LOADING CASE INSIDE WIDTH	1740mm
DIMENSIONS; LENGHT/WIDTH/HEIGHT	3000/1900/800mm
TOTAL LENGHT/WIDTH/YÜKSEKLİK	3900/1900/1800mm
PLARFORM HEIGHT MEASURED FROM FLOOR	990mm
SIDEWALL HEIGHT	800mm
FLOOR THICKNESS (mm)	4mm
WALL THICKNESS (mm)	4mm
WHEEL TRACK	1600mm
SUSPENSION	Optiona
TYRES	Optiona
MAXIMUM SPEED	25km
TIPPING SYSTEM	Optiona
TELESCOPIC CYLINDER (Piston Stage/Oil Required/Working Pressure)	3 Stage/8 lt/1
BRAKE TYPE	Optiona
CHASSIS	140NPU
MINIMUM TRACTOR POWER REQUIREMENT	50HP
TIPPING ANGLE (Backwards/Sides)	40
OPTIONALS	
TIPPING SYSTEM	BACK TIPPING -
BRAKE TYPE	HYDRAULIC BRA
SUSPENSION	LEAF SPRING / 1
	900/16 1985
TYRES	
	✓
TOP & BOTTOM OPENABLE LIDS	✓
REAR BRAKE OUTPUT	✓
REAR DAMPER OIL OUTLET	✓
REAR TOWBAR	✓
WHEEL JACK	✓
HYDRAULIC JACK	✓
EXTRA ADDITIONAL	✓
HEAVY COVER	✓
LADER	✓
PLASTIC TOOL CABINET	✓

TIPPING POOL BOX

SERVET
AGRICULTURAL
MACHINES



SINGLE AXLE BACK TIPPING POOL BOX			
	5T	6T	8T
	SERVET	SERVET	SERVET
TPB	SRVT50SABTPB	SRVT60SABTPB	SRVT80SABTPB
	5000kg	7560kg	9750kg
	5177kg	6000kg	8000kg
	1450kg	6269kg	7560kg
	5,39m3	1560kg	1750kg
	6m2	6,53m3	7,87m3
	3267mm	7,26m2	7,87m2
	1834mm	3560mm	3860mm
	3400/2000/900mm	2040mm	2040mm
	4470/3470/1950mm	3700/2100/900mm	4460/2200/1000mm
	965mm	4950/2100/2600mm	5220/2200/2100mm
	900mm	970mm	1100mm
	4mm	900mm	1000mm
	4mm	4mm	4mm
	4mm	4mm	4mm
	1600mm	1600mm	1600mm
	Optional	Optional	Optional
	Optional	Optional	Optional
	25km	25km	40km
	Optional	Optional	Optional
50 bar	3 Stage/8 lt/160 bar	3 Stage/12 lt/160 bar	4 Stage/18 lt/160 bar
	Optional	Optional	Optional
	180NPU	180NPU	180NPU
	50HP	75HP	75HP
	40	40	40

THREE SIDES TIPPING			
BRAKE / PNEUMATIC BRAKE			
PARABOLIC			
	900/16 1985	900/16 1985	400/60-15.5 3549
	12.5/80-15.3 5300	400/60-15.5 3549	500/50-17.5 6186
		12.5/80-15.3 5300	
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓

TO VIEW ON
THE WEBSITE



TANDEM AXLE BACK



TECHNICAL SPECIFICATIONS			
PRODUCT DESCRIPTION			
LOADING TONNAGE	6T	8T	10T
BRAND NAME	SERVET	SERVET	SERVET
PRODUCT CODE	SRVT60TABTPB	SRVT80TABTPB	SRVT100TABTPB
ALLOWABLE TOTAL WEIGHT	7850kg	10600kg	12750kg
LOADING CAPACITY	6000kg	8000kg	10000kg
LOADING CAPACITY (Wheat 1Ton=1,041m3)	7645kg	8845kg	10362kg
EMPTY WEIGHT	1850kg	2600kg	2750kg
LOAD VOLUME	7,96m3	9,21m3	10,79m3
LOADING SPACE	7,96m2	8,375m2	9m2
LOADING CASE INSIDE LENGHT	3860mm	4060mm	4360mm
LOADING CASE INSIDE WIDTH	2063mm	2063mm	2063mm
DIMENSIONS; LENGHT/WIDTH/HEIGHT	4000/2200/1000mm	4200/2200/1100mm	4500/2200/1200mm
TOTAL LENGHT/WIDTH/YÜKSEKLİK	5180/2350/2030mm	5380/2350/2130mm	5885/2350/2230mm
PLARFORM HEIGHT MEASURED FROM FLOOR	1030mm	1030mm	1030mm
SIDEWALL HEIGHT	1000mm	1100mm	1200mm
FLOOR THICKNESS (mm)	4mm	4mm	4mm
WALL THICKNESS (mm)	4mm	4mm	4mm
WHEEL TRACK	1700mm	1700mm	1700mm
SUSPENSION	Optional	Optional	Optional
TYRES	Optional	Optional	Optional
MAXIMUM SPEED	40km	40km	40km
TIPPING SYSTEM	Optional	Optional	Optional
TELESCOPIC CYLINDER (Piston Stage/Oil Required/Working Pressure)	4 Stage/18 lt/160 bar	4 Stage/18 lt/160 bar	4 Stage/18 lt/160 bar
BRAKE TYPE	Optional	Optional	Optional
CHASSIS	180NPU	180NPU	200NPU
MINIMUM TRACTOR POWER REQUIREMENT	55HP	70HP	70HP
TIPPING ANGLE (Backwards/Sides)	40	40	40
OPTIONALS			
TIPPING SYSTEM			
BRAKE TYPE			
SUSPENSION			
TYRES			
TOP & BOTTOM OPENABLE LIDS			
REAR BRAKE OUTPUT	✓	✓	✓
REAR DAMPER OIL OUTLET	✓	✓	✓
REAR TOWBAR	✓	✓	✓
WHEEL JACK	✓	✓	✓
HYDRAULIC JACK	✓	✓	✓
EXTRA ADDITIONAL	✓	✓	✓
HEAVY COVER	✓	✓	✓
LADER	✓	✓	✓
PLASTIC TOOL CABINET	✓	✓	✓
PLASTIC WATER TANK	✓	✓	✓
SPARE TYRE	✓	✓	✓

**SERVET
AGRICULTURAL
MACHINES**


TO VIEW ON
THE WEBSITE





TECHNICAL SPECIFICATIONS	
PRODUCT DESCRIPTION	
LOADING TONNAGE	3T
BRAND NAME	SERVET
PRODUCT CODE	SRVT30SAT
ALLOWABLE TOTAL WEIGHT	3800kg
LOADING CAPACITY	3000kg
LOAD VOLUME	3m3
EMPTY WEIGHT	800kg
TANK LENGHT	2500mm
TANK DIAMETER	1260mm
DIMENSIONS; LENGHT/WIDTH/HEIGHT	2295/1452/1122mm
TOTAL LENGHT/WIDTH/YÜKSEKLİK	4115/1862/1952mm
TANK THICKNESS (mm)	3mm
CENTRIFUGAL	Optional
WHEEL TRACK	1600mm
SUSPENSION	Optional
TYRES	Optional
MAXIMUM SPEED	25km
BRAKE TYPE	Optional
CHASSIS	100NPU
MINIMUM TRACTOR POWER REQUIREMENT	45HP
OPTIONALS	
BRAKE TYPE	HYDRAULIC BRAKE / PNEUMATIC B
SUSPENSION	LEAF SPRING / PARABOLIC
TYRES	750/16 1394 10.0/75-15.3 1599
REAR BRAKE OUTPUT	✓
REAR DAMPER OIL OUTLET	✓
REAR TOWBAR	✓
WHEEL JACK	✓
HYDRAULIC JACK	✓
LADER	✓
PLASTIC TOOL CABINET	✓
PLASTIC WATER TANK	✓
SPARE TYRE	✓

**SERVET
AGRICULTURAL
MACHINES**



TO VIEW ON
THE WEBSITE





TECHNICAL SPECIFICATIONS	
PRODUCT DESCRIPTION	
LOADING TONNAGE	3T
BRAND NAME	SERVET
PRODUCT CODE	SRVT30DAT
ALLOWABLE TOTAL WEIGHT	4080kg
LOADING CAPACITY	3000kg
LOAD VOLUME	3m3
EMPTY WEIGHT	1080kg
TANK LENGHT	2500mm
TANK DIAMETER	1260mm
DIMENSIONS; LENGHT/WIDTH/HEIGHT	3975/1442/1070mm
TOTAL LENGHT/WIDTH/YÜKSEKLİK	4795/1862/1900mm
TANK THICKNESS (mm)	3mm
CENTRIFUGAL	Optional
WHEEL TRACK	1600mm
SUSPENSION	Optional
TYRES	Optional
MAXIMUM SPEED	25km
BRAKE TYPE	Optional
CHASSIS	100NPU
MINIMUM TRACTOR POWER REQUIREMENT	55HP
OPTIONALS	
BRAKE TYPE	HYDRAULIC BRAKE / PNEUMATIC
SUSPENSION	LEAF SPRING / PARABOLIC
TYRES	10.0/80-12 1843
REAR BRAKE OUTPUT	✓
REAR DAMPER OIL OUTLET	✓
REAR TOWBAR	✓
WHEEL JACK	✓
HYDRAULIC JACK	✓
LADER	✓
PLASTIC TOOL CABINET	✓
PLASTIC WATER TANK	✓
SPARE TYRE	✓

AXLE TANKERS

SERVET
AGRICULTURAL
MACHINES



DOUBLE AXLE TANKERS			
	5T	6T	8T
	SERVET	SERVET	SERVET
	SRVT50DAT	SRVT60DAT	SRVT80DAT
	6230kg	7600kg	9700kg
	5000kg	6000kg	8000kg
	5m3	6m3	
	1230kg	1600kg	1700kg
	3000mm	3580mm	4380mm
	1310mm	1670mm	1580mm
	4760/1470/1070mm	4030/1470/10200mm	4300/1704/1020mm
	5580/1890/1900mm	5850/1890/1850mm	6120/2124/1850mm
	3mm	3mm	3mm
	Optional	Optional	Optional
	1600mm	1700mm	1700mm
	Optional	Optional	Optional
	Optional	Optional	Optional
	25km	25km	25km
	Optional	Optional	Optional
	120NPU	140NPU	140NPU
	55HP	55HP	70HP
BRAKE			
	750/16 1394	11.5/80-15.3 2464	12.5/80-15.3 5300
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓

TO VIEW ON
THE WEBSITE





TECHNICAL SPECIFICATIONS

PRODUCT DESCRIPTION

LOADING TONNAGE

BRAND NAME

PRODUCT CODE

ALLOWABLE TOTAL WEIGHT

LOADING CAPACITY

LOAD VOLUME

EMPTY WEIGHT

TANK LENGHT

TANK DIAMETER

DIMENSIONS; LENGHT/WIDTH/HEIGHT

TOTAL LENGHT/WIDTH/YÜKSEKLİK

TANK THICKNESS (mm)

CENTRIFUGAL

WHEEL TRACK

SUSPENSION

TYRES

MAXIMUM SPEED

BRAKE TYPE

CHASSIS

MINIMUM TRACTOR POWER REQUIREMENT

OPTIONALS

BRAKE TYPE

SUSPENSION

TYRES

REAR BRAKE OUTPUT

REAR DAMPER OIL OUTLET

REAR TOWBAR

WHEEL JACK

HYDRAULIC JACK

LADER

PLASTIC TOOL CABINET

PLASTIC WATER TANK

SPARE TYRE

AXLE TANKERS

SERVET
AGRICULTURAL
MACHINES



TANDEM AXLE TANKERS			
6T	7T	8T	10T
SERVET	SERVET	SERVET	SERVET
SRVT60TAT	SRVT70TAT	SRVT80TAT	SRVT100TAT
7300kg	8550kg	9700kg	
6000kg	7000kg	8000kg	10000kg
1300kg	1550kg	1700kg	1840mm
4020mm	4180mm	4380mm	4620mm
1430mm	1540mm	1580mm	1610mm
6050/2124/1780mm	6080/2124/1780mm	6120/2124/1850mm	6450/2124/1850mm
3mm	3mm	3mm	4mm
Optional	Optional	Optional	Optional
1600mm	1600mm	1700mm	1700mm
Optional	Optional	Optional	Optional
Optional	Optional	Optional	Optional
25km	25km	25km	25km
Optional	Optional	Optional	Optional
140NPU	180NPU	200NPU	200NPU
70HP	70HP	70HP	70HP
HYDRAULIC BRAKE / PNEUMATIC BRAKE			
AF SPRING / PARABOLIC			
12.5/80-15.3	12.5/80-15.3	12.5/80-15.3	400/60-15.5
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓

TO VIEW ON
THE WEBSITE



The logo for Served, featuring the word "Served" in a white, cursive script font, set against a teal rectangular background.

Served

**SERVET
AGRICULTURAL
MACHINES**



Phone

+90 532 337 37 91

Mail

info@7kardesler.com.tr

Web Site

www.7kardesler.com.tr

Address

Balıkesir/Burhaniye 10700