

ATTACHMENTS



FOR DETAILS OF PRODUCT SIZE PARAMETERS, PLEASE CALL US

SHANDONG OUJIN ENGINEERING MACHINERY CO.,LTD.

Add: Shandong Qingzhou Caterpillar Industrial Park Tel: +86-536 2136789 15006692900
 E-mail: han@eougem.com Web: www.eougem.com www.mammutequip.com www.miniwheelloader.com



20 YEARS PRODUCTION EXPERIENCE



PRODUCT BROCHURE

SHANDONG OUJIN ENGINEERING MACHINERY CO.,LTD

Make your work easier and faster.
Various accessories greatly improve work efficiency and save your time

ONE-STOP SERVICE

ABOUT US

SHANDONG OUJIN ENGINEERING MACHINERY CO.,LTD

Shandong OUJIN Engineering Machinery Co.,Ltd is mainly engaged in the production and management of the construction machinery of medium and small loaders etc,which mainly produces the MAMMUT series of engineering mechanical deformation products such as wheel loaders of 1-6TON,motor grader ,3-3.5 TON terrain forklift ,telescopic loader ,MAMMUT grass grasping machine,wooden grabbing machine and snow grader machine.MAMMUT covers an area of 50000 square meters of production plant currently.In the early of 2011,a high quality and modern plant as well as a research and development center will be established at the third stage of engineering at Caterpillar Industrial Park according to the company development strategy.It is with a total investment of 320 million yuan ,covering an area of 35000 square meters ,with unusual sales revenue of over 230 million yuan which is of high standards and high quality.MAMMUT has a first class R&D team ,a first class manufacturing team and a first class after-sales service team .It passed ISO9001 international quality management system certification and European CE certificate in one time . The products of MAMMUT are always in sync with the advanced level of the world and shaping a new image of MAMMUT.



Oujin Machinery adheres to scientific development, attaches importance to market demand as the guide, and advances in research and development and production simultaneously.It has successively introduced a large number of advanced production equipment at home and abroad, and the high-end manufacturing capacity of the enterprise has continued to improve.



Robot Welding



Power coating



Our Stock



ELECTRIC LOADER



SK650 ELECTRIC

Type	Electric Skid Steer Loader
Dimension	2170*830*1355
Machine Weight	900 kg
Battery	LiFePO4 228ah/16.4kwh
Rated loading	280kg/616lbs
Max. lift	350kg/770lbs
Max. travel speed	6km/h
Bucket Capacity	0.15m³
Charging Time	7Hours
Hydraulic Flow	15.8gpm (60L/min)



WLE06

Bucket capacity	0.3m³
Bucket width	1200mm
Rated loading	500kg
Dimension	2836X1010X2110
Dumping height	1751mm
Operating weight	1200kg
Max speed	10km
Tire	23*8.5-12
Battery	LEAD ACID 5.8Kwh
Drive motor	8Hp(Peak)
Hydraulic motor	4Hp(Peak)
Charging Time	4Hours



WLE26

Bucket capacity	0.43m³
Bucket width	1200mm
Rated loading	800kg
Dimension	3849*2296*1250
Operating weight	1850kg
Max speed	20km
Tire	26X12-12
Battery	LEAD ACID 14.4Kwh
	LiFePO4 320ah/15.36Kwh
Drive motor	10.8Hp
Hydraulic motor	6.75Hp
Charging Time	7Hours



WLE35

Bucket capacity	0.43m³
Bucket width	1400mm
Rated loading	1200kg
Dimension	4242x1400x2245
Dumping height	2205mm
Operating weight	2550kg
Max speed	20km
Tire	31X15.5-15(10/75-15.3)
Battery	LiFePO4 460ah/23Kwh
Drive motor	22.41Hp
Hydraulic motor	21Hp
Charging Time	5.7Hours

WHEEL LOADER



Tier 4
Stage V

WLO8

Bucket capacity	0.3m ³
Operating weight(standard)	1560kg
Rated loading	600kg
Dimension	3119x911x2114mm
Dumping height	1701mm
Ground clearance	274mm
Wheel base	1281mm
Operating weight	1360kg
Engine	Perkins/Kubota
Rated power	25HP
Max speed	10km
Oil tank	30L



Tier 4
Stage V

WL12

Bucket capacity	0.4m ³
Bucket width	1480mm
Rated loading	1000kg
Dimension	4424x1480x2523mm
Dumping height	1810mm
Ground clearance	249mm
Wheel base	1785mm
Operating weight	3300kg
Engine	XINCHAI/YUNNEI/YANMAR CUMMINS/PERKINS/KOHLER
Max speed	25km
Oil tank	65L
Tire	12-16.5/31X15.5-15



Tier 4
Stage V

WL35

Bucket capacity	0.6m ³
Bucket width	1400mm
Rated loading	1200kg
Dimension	4242x1400x2245mm
Dumping height	2205mm
Ground clearance	240mm
Wheel base	1681mm
Operating weight	2550kg
Engine	Kubota/Kohler
Max speed	20km
Oil tank	50L
Tire	31X15.5-15(10/75-15.3)



Tier 4
Stage V

WL16

Bucket capacity	0.6m ³
Bucket width	1640mm
Rated loading	1500kg
Dimension	5110x1780x2496mm
Dumping height	2762mm
Ground clearance	249mm
Wheel base	1995mm
Operating weight	3600kg
Engine	XINCHAI/YUNNEI/YANMAR CUMMINS/PERKINS/KOHLER
Max speed	25km
Oil tank	65L
Tire	23.5/70-16 (20.5)



WL26

Bucket capacity	0.4m ³
Wheel base	1400mm
Rated loading	800kg
Dimension	3849x2296x1250mm
Dumping height	1751mm
Dump distance	700mm
Min turning radius	875mm
Operating weight	1770kg
Overall weight	1950kg
Rated power	25HP
Engine	Perkins/Kubota
Max speed	10km



Tier 4
Stage V



Tier 4
Stage V

WL18

Bucket capacity	0.6m ³
Bucket width	1640mm
Rated loading	1800kg
Dimension	5110x1780x2496mm
Dumping height	2772mm
Ground clearance	249mm
Wheel base	1995mm
Operating weight	3800kg
Engine	XINCHAI/YUNNEI/YANMAR CUMMINS/PERKINS/KOHLER
Max speed	25km
Oil tank	65L
Tire	23.5/70-16 (20.5)



Tier 4
Stage V

WL20

Bucket capacity	1m ³
Bucket width	2040mm
Rated loading	2000kg
Dimension	5960x2010x2850mm
Dumping height	3400mm
Ground clearance	340mm
Wheel base	2430mm
Operating weight	5500kg
Engine	XINCHAI/YUNNEI/YANMAR CUMMINS/PERKINS/KOHLER
Max speed	25km
Oil tank	82L
Tire	16/70-20

TELESCOPIC LOADER



Tier 4
Stage V

TL800

Bucket capacity	0.3m ³
Bucket width	1100mm
Rated loading	600kg
Dimension	3363x911x2124mm
Dumping height	2269mm
Ground clearance	274mm
Wheel base	1281mm
Operating weight	1720kg
Engine	KUBOTA/PERKINS
Max speed	10km
Oil tank	30L
Tire	24*13-12



Tier 4
Stage V

WL26T

Bucket capacity	0.4m ³
Bucket width	1350mm
Rated loading	800kg
Dimension	3956x1250x2300mm
Dumping height	3199mm
Ground clearance	278mm
Wheel base	1557mm
Operating weight	2200kg
Engine	KUBOTA/PERKINS
Max speed	10km
Oil tank	50L
Tire	27/10.5-15 (26/12-12)



Tier 4
Stage V

TL2500

Bucket capacity	1.2m ³
Bucket width	1800mm
Rated loading	2500kg
Dimension	6687x2014x2900mm
Dumping height	3873mm
Ground clearance	350mm
Wheel base	2573mm
Operating weight	6800kg
Engine	XINCHAI/YANMAR YUNNEI/CUMMINS
Max speed	38km
Oil tank	82L
Tire	405/70-24



Tier 4
Stage V

TL3000

Bucket capacity	1.5m ³
Bucket width	2000mm
Rated loading	3000kg
Rated Power	92kw
Dimension	7400x2015x2949mm
Dumping height	4428mm
Ground clearance	370mm
Wheel base	2687mm
Operating weight	7500kg
Engine	WEICHAI/YUNNEI/CUMMINS
Service Brake	Four wheel drive
Tire	17.5-25



Tier 4
Stage V

TL1600

Bucket capacity	0.6m ³
Bucket width	1640mm
Rated loading	1600kg
Dimension	6000x1780x2680mm
Dumping height	4200mm
Ground clearance	249mm
Wheel base	2050mm
Operating weight	4300kg
Engine	XINCHAI/YANMAR YUNNEI/CUMMINS
Max speed	25km
Oil tank	65L
Tire	20.5/70-16



Tier 4
Stage V

TL1800

Bucket capacity	0.8m ³
Bucket width	1640mm
Rated loading	1800kg
Dimension	5437x1700x2470mm
Dumping height	4030mm
Ground clearance	249mm
Wheel base	2366mm
Operating weight	4500kg
Engine	XINCHAI/YANMAR YUNNEI/CUMMINS
Max speed	25km
Oil tank	65L
Tire	23.5/70-16



Tier 4
Stage V

TL3500

Bucket capacity	1.7m ³
Bucket width	2000mm
Rated loading	3500kg
Rated Power	92kw
Dimension	7400x2015x2949mm
Dumping height	4428mm
Ground clearance	370mm
Wheel base	2687mm
Operating weight	7800kg
Engine	WEICHAI/YUNNEI/CUMMINS
Service Brake	Four wheel drive
Tire	17.5-25

TL4000

Bucket capacity	2m ³
Bucket width	2000mm
Rated loading	4000kg
Rated Power	103kw
Dimension	8700x2350x3300mm
Dumping height	4428mm
Ground clearance	370mm
Wheel base	2687mm
Operating weight	10500kg
Engine	WEICHAI/CUMMINS
Service Brake	Four wheel drive
Tire	20.5-25



Tier 4
Stage V



ROUGH TERRAIN FORKLIFT



H20/25

Rated loading	2000/2500kg
Dimension	3030x1650x2105mm
Height	3831mm
Ground clearance	260mm
Wheel base	1800mm
Operating weight	4000/4300kg
Engine	KUBOTA/PERKINS/KOHLER
Max speed	20km
Oil tank	65L
Tire	400/70-20



H30/35

Rated loading	3000/3500kg
Dimension	4594x1720x2224mm
Height	4500mm
Ground clearance	280mm
Wheel base	1800mm
Operating weight	5700/6000kg
Engine	CUMMINS/KUBOTA/KOHLER
Max speed	20/35km
Oil tank	65L
Tire	12-16.5



CPCY20

Rated loading	2000kg
Dimension	3500x2550x3708mm
Height	3000mm
Ground clearance	206mm
Wheel base	1785mm
Operating weight	3200kg
Engine	YUNNEI
Load center distance	565mm
Drive Mean	Four Wheel drive
Max climbing power(%)	30
Tire	12-16.5



CPCY30

Rated loading	3000kg
Dimension	4000x1800x2750mm
Height	3000mm
Ground clearance	270mm
Wheel base	2100mm
Operating weight	4680kg
Engine	YUNNEI
Load center distance	500mm
Full load liftingspeed	380mm/s
Max speed	30km
Tire	tire:12-16.5

CPCY40/50

Rated loading	4000/5000kg
Dimension	6000x2080x2950mm
Fuill Height when max lifting	4500mm
Height of the mast	3500mm
Ground clearance	260/300mm
No fork Length	4680mm
Drive Mean	Four Wheel drive
Max speed	35km
Tire	16/90-24



SKID STEER LOADER



**Tier 4
Stage V**

**YOUR
DESIGN
HERE**

SK1250

Dimension	2900*1067*1543
Machine Weight	1550 kg
Engine Model	kubota/perkins
Rated operating capacity	544kg/1200lbs
Tipping capacity	1341kg/2958lbs
Max. travel speed	7km/h
Bucket Capacity	0.2m ³
Ground Clearance	180mm/7inc
Fuel tank capacity	54.9L
Hydraulic Flow	15gpm (56L/min)



**Tier 4
Stage V**

**YOUR
DESIGN
HERE**

SK650W

Type	Skid Steer Loader
Dimension	2170*830*1355
Machine Weight	900 kg
Engine Model	Honda, Briggs&Stratton; Rato
Mini skid steer rated loading	280kg/616lbs
Max. lift	350kg/770lbs
Max. travel speed	6km/h
Bucket Capacity	0.15m ³
Operating weight	900kg/1980lbs
Hydraulic Flow	15gpm (56L/min)
Engine displacement	680ml
Rated power	23hp/17kw



**Tier 4
Stage V**

**YOUR
DESIGN
HERE**

SK650

Type	Skid Steer Loader
Dimension	2170*830*1355
Machine Weight	900 kg
Engine Model	Honda, Briggs&Stratton; Rato
Mini skid steer rated loading	280kg/616lbs
Max. lift	350kg/770lbs
Max. travel speed	5km/h
Bucket Capacity	0.15m ³
Operating weight	900kg/1980lbs
Hydraulic Flow	15gpm (56L/min)
Engine displacement	680ml
Rated power	23hp/17kw



**Tier 4
Stage V**

**YOUR
DESIGN
HERE**

SK950

Engine model	Kubota /Perkins diesel
No. of cylinders	3 cylinder
Operating height	2695mm
Height to bucket hinge pin	2000mm
Height to top	1496mm
Wheelbase	1080mm
Overall width	1070mm
Mini ground clearance	94mm
Rated loading capacity	400kg/950lbs
Machine weight	1330kg
Hydraulic Flow	15gpm (56L/min)



OJ50-C

Operating load	700kg
Max Speed	10km/h
Fuel tank capacity	50L
Tire (track) model	300X52.5
Rated power	50Hp
Dead weight	3000kg
Self weight bucket	2800kg
Bucket capacity	0.3m ³
Dumping height	2100mm
Dumping reach	790mm
Tread width	1102mm



OJ65-C

Operating load	1000kg
Max Speed	12km/h
Fuel tank capacity	90L
Tire (track) model	320X84
Rated power	74Hp
Dead weight	4200kg
Self weight bucket	3800kg
Bucket capacity	0.5m ³
Dumping height	2230mm
Dumping reach	715mm
Tread width	1462mm



OJ60-W

Operating load	850kg
Max Speed	12km/h
Fuel tank capacity	75L
Tire (track) model	12-16.5
Rated power	60Hp
Dead weight	3200kg
Self weight bucket	2800kg
Bucket capacity	0.4m ³
Dumping height	2400mm
Dumping reach	750mm
Tread width	1500mm



OJ100-W

Operating load	1100kg
Max Speed	12km/h
Fuel tank capacity	75L
Tire (track) model	12-16.5
Rated power	100Hp
Dead weight	4000kg
Self weight bucket	3550kg
Bucket capacity	0.55m ³
Dumping height	2450mm
Dumping reach	700mm
Tread width	1500mm



OJ100-C

Operating load	1200kg
Max Speed	12km/h
Fuel tank capacity	90L
Tire (track) model	320X84
Rated power	100Hp
Dead weight	4800kg
Self weight bucket	4500kg
Bucket capacity	0.55m ³
Dumping height	2450mm
Dumping reach	700mm
Tread width	1654mm



OJ45-W

Operating load	700kg
Max Speed	12km/h
Fuel tank capacity	62.5L
Tire (track) model	10-16.5
Rated power	50Hp
Dead weight	3000kg
Self weight bucket	2700kg
Bucket capacity	0.4m ³
Dumping height	2380mm
Dumping reach	700mm
Tread width	1450mm





Tier 4
Stage V

GEM926

Bucket capacity	0.9m ³
Bucket width	2000mm
Rated loading	1800kg
Dimension	5900x1900x2800mm
Dumping height	3200mm
Wheel base	2120mm
Operating weight	4540kg
Engine	Yunnei
Max speed	25km
Oil tank	80L
Tire	16/70-20



Tier 4
Stage V

GEM930

Bucket capacity	1.0m ³
Bucket width	2000mm
Rated loading	2000kg
Dimension	5960x2010x2850mm
Dumping height	3200mm
Wheel base	2430mm
Operating weight	5500kg
Engine	Yunnei
Max speed	30km
Oil tank	80L
Tire	16/70-20



Tier 4
Stage V

GEM938

Bucket capacity	1.3m ³
Bucket width	2200mm
Rated loading	2800kg
Dimension	6240x2200x2920mm
Dumping height	3430mm
Rated Power	92kw
Wheel base	2430mm
Operating weight	6500kg
Engine	Weichai/Cummins/Yunnei
Max speed	23km
Service Brake	Four wheel drive
Tire	16/90-24



Tier 4
Stage V

GEM636

Bucket capacity	1.5m ³
Bucket width	2200mm
Rated loading	3600kg
Dimension	7120x2137x2440mm
Dumping height	3300mm
Lifting height	5200 mm
Rated Power	92kw
Wheel base	2770mm
Operating weight	10000kg
Engine	Weichai
Service Brake	Four wheel drive
Tire	17.5-25

CONSTRUCTION INDUSTRY LOADER



GEM650

Bucket capacity	3m ³
Rated loading	5000kg
Dimension	8247x3068x3409mm
Dumping height	3200mm
Rated Power	162kw
Wheel base	3300mm
Operating weight	16200kg
max gradeability	30°
Engine	Weichai
Service Brake	Four wheel drive
Oil tank	273L
Tire	23.5-25



Tier 4
Stage V