



ABOUT US

SHANDONG OUJIN ENGINEERING MACHINERY CO.,LTD

Shandong OUJIN Engineering Machinery Co., Ltd. is mainly engaged in the production and management of the construction machinery of medium and small loaders etc.now we have two brands EOUGEM and MAMMUT, it mainly produce 1-6 ton wheel loaders and other engineering machinery deformation products.such as mini electric loader ,skid steer loader ,3-5ton terrain forklift,1-4ton telescopic loader, EOUGEM and MAMMUT covers an area of 50,000 square meters of production plant currently. In the early of 2011, a high quality and modern plant as well as a research and development center will be established at the third stage of engineering at Caterpillar Industrial Park according to the company's development strategy. It is with a total investment of 320 million yuan, covering an area of 35,000 square meters, with annual sales revenue of over 230 million yuan which is of high standards and high quality. EOUGEM and MAMMUT has a first-class R & D team, a first-class manufacturing team and a first-class after-sales service team. It passed ISO9001 international quality management system certification And passed CE, EAC, TUV ,EPA4 engine ,EURO3 engine ,EURO5 engine certificates to meet customer requirements. The products of EOUGEM and MAMMUT are always in sync with the advanced level of the world and shaping a new image of EOUGEM and MAMMUT.



EOUGEM



Professional forklift manufacturer





CPCD15

Rated capacity	1500kg
Lift height	3000-6000mm
Mast lowered height	1995mm
Length(Without Fork)	2255mm
Width	1070 mm
Height	1995 mm
Tires	6.50-10/5.00-8
Wheel base	1410mm
Turning Radius (outside)	1955mm
Service weight	2660kg
Engine Model	Xinchai 485
Rated power	37kw



CPCD20

Rated capacity	2000kg
Lift height	3000-6000mm
Mast lowered height	2070mm
Length(Without Fork)	2590mm
Width	1150mm
Height	2070mm
Tires	7.00-12-12/6.00-9-10
Wheel base	1600mm
Turning Radius (outside)	2310mm
Service weight	3590kg
Engine Model	Xinchai C490BPG
Rated power	40kw



CPCD35

Rated capacity	3500kg
Lift height	3000-6000mm
Mast lowered height	2095mm
Length(Without Fork)	2730mm
Width	1225 mm
Height	2130 mm
Tires	28X9-15-12PR/6.50-10-10PR
Wheel base	1700mm
Turning Radius (outside)	2510mm
Service weight	4500kg
Engine Model	Xinchai C490BPG
Rated power	40kw



CPCD40

Rated capacity	4000kg
Lift height	3000-6000mm
Mast lowered height	2270mm
Length(Without Fork)	2850mm
Width	1250mm
Height	2170mm
Tires	28X9-15NHS/6.50-10-10NHS
Wheel base	2100mm
Turning Radius (outside)	2910mm
Service weight	5250kg
Engine Model	Xinchai C495BPG
Rated power	42kw



CPCD25

Rated capacity	2500kg
Lift height	3000-6000mm
Mast lowered height	2070mm
Length(Without Fork)	2595 mm
Width	1150 mm
Height	2070 mm
Tires	7.00-12-12/6.00-9-10
Wheel base	1600mm
Turning Radius (outside)	2310mm
Service weight	3790kg
Engine Model	Xinchai C490BPG
Rated power	40kw



CPCD30

Rated capacity	3000kg
Lift height	3000-6000mm
Mast lowered height	2110mm
Length(Without Fork)	2682mm
Width	1225mm
Height	2160mm
Tires	28X9-15-12PR/6.50-10-10PR
Wheel base	1700mm
Turning Radius (outside)	2400mm
Service weight	4270kg
Engine Model	Xinchai C490BPG
Rated power	40kw



CPCD50

Rated capacity	5000kg
Lift height	3000-6000mm
Mast lowered height	2340mm
Length(Without Fork)	2990 mm
Width	1370mm
Height	2170mm
Tires	300-15/7.00-12
Wheel base	2040mm
Turning Radius (outside)	2700mm
Service weight	5700kg
Engine Model	Xinchai A498BPG
Rated power	45kw



CPCD70

Rated capacity	7000kg
Lift height	3000-6000mm
Mast lowered height	2500mm
Length(Without Fork)	3565mm
Width	2010mm
Height	2430mm
Tires	8.25-15-14PR
Wheel base	2250mm
Turning Radius (outside)	3350mm
Service weight	9750kg
Engine Model	Xichai CA6110
Rated power	85kw



CPYD15

Rated capacity	1500kg
Lift height	3000-6000mm
Mast lowered height	2095mm
Length(Without Fork)	2255mm
Width	1070mm
Height	1995mm
Tires	6.50-10/5.00-8
Wheel base	1410mm
Turning Radius (outside)	1955mm
Service weight	2660kg
Engine Model	Nissan K21
Rated power	31.2kw



CPYD20

Rated capacity	2000kg
Lift height	3000-6000mm
Mast lowered height	2095mm
Length(Without Fork)	2480mm
Width	1150mm
Height	2120mm
Tires	7.00-12-12/6.00-9-10
Wheel base	1600mm
Turning Radius (outside)	2310mm
Service weight	3590kg
Engine Model	Nissan K21
Rated power	31.2kw



CPYD30

Rated capacity	3000kg
Lift height	3000-6000mm
Mast lowered height	2110mm
Length(Without Fork)	2680mm
Width	1225mm
Height	2160mm
Tires	28x9-15-12/6.50-10-10PR
Wheel base	1700mm
Turning Radius (outside)	2400mm
Service weight	4270kg
Engine Model	Nissan K25
Rated power	37.4kw



CPYD35

Rated capacity	3500kg
Lift height	3000-6000mm
Mast lowered height	2095mm
Length(Without Fork)	2680mm
Width	1225mm
Height	2130mm
Tires	28x9-15-12/6.50-10-10PR
Wheel base	1700mm
Turning Radius (outside)	2510mm
Service weight	4500kg
Engine Model	Nissan K25
Rated power	37.4kw



CPYD25

Rated capacity	2500kg
Lift height	3000-6000mm
Mast lowered height	2095mm
Length(Without Fork)	2630mm
Width	1150mm
Height	2120mm
Tires	7.00-12-12PR
Wheel base	1650mm
Turning Radius (outside)	2380mm
Service weight	3790kg
Engine Model	Nissan K21
Rated power	31.2kw



CPYD40

Rated capacity	4000kg
Lift height	3000-6000mm
Mast lowered height	2270mm
Length(Without Fork)	2850mm
Width	1250mm
Height	2130mm
Tires	28x9-15-12/6.50-10-10PR
Wheel base	2100mm
Turning Radius (outside)	2910mm
Service weight	5250kg
Engine Model	Nissan K25
Rated power	37.4kw



CPYD50

Rated capacity	5000kg
Lift height	3000-6000mm
Mast lowered height	2340mm
Length(Without Fork)	2990mm
Width	1650mm
Height	2170mm
Tires	300-15/7.00-12
Wheel base	2250mm
Turning Radius (outside)	3250mm
Service weight	5700kg
Engine Model	Nissan K25
Rated power	37.4kw

» **Electric Forklift**



CPD10

Rated capacity	1000kg
Lift height	3000-6000mm
Mast lowered height	2017mm
Length(Without Fork)	1980mm
Width	1020mm
Height	1847mm
Tires	15X4 1/2-8/15X4 1/2-8
Wheel base	1330mm
Turning Radius (outside)	2050mm
Service weight	1550kg
Battery Type	Lead Acid
Battery Capacity	60V/120Ah



CPD15

Rated capacity	1500kg
Lift height	3000-6000mm
Mast lowered height	2030mm
Length(Without Fork)	2230mm
Width	1160mm
Height	2110mm
Tires	650-10/16X6-8
Wheel base	1460mm
Turning Radius (outside)	2240mm
Service weight	2300kg
Battery Type	Lead Acid
Battery Capacity	60V/180Ah



CPD30

Rated capacity	3000kg
Lift height	3000-6000mm
Mast lowered height	2057mm
Length(Without Fork)	2600mm
Width	1225mm
Height	2200mm
Tires	28x9-15/18x7-8
Wheel base	1850mm
Turning Radius (outside)	2300mm
Service weight	4150kg
Battery Type	Lead Acid
Battery Capacity	72V/260Ah



CPD50

Rated capacity	5000kg
Lift height	3000-6000mm
Mast lowered height	2340mm
Length(Without Fork)	2990mm
Width	1585mm
Height	2350mm
Tires	250-10/21X8-9
Wheel base	2040mm
Turning Radius (outside)	2700mm
Service weight	7100kg
Battery Type	Lead Acid
Battery Capacity	80V/350Ah



CPD20

Rated capacity	2000kg
Lift height	3000-6000mm
Mast lowered height	2030mm
Length(Without Fork)	2230mm
Width	1160mm
Height	2110mm
Tires	650-10/16X6-8
Wheel base	1460mm
Turning Radius (outside)	2240mm
Service weight	2900kg
Battery Type	Lead Acid
Battery Capacity	60V/210Ah



CPD25

Rated capacity	2500kg
Lift height	3000-6000mm
Mast lowered height	2030mm
Length(Without Fork)	2330mm
Width	1160mm
Height	2110mm
Tires	650-10/16X6-8
Wheel base	1600mm
Turning Radius (outside)	2370mm
Service weight	3300kg
Battery Type	Lead Acid
Battery Capacity	72V/210Ah

Rated capacity	3000/3500kg
Lift height	3000-6000mm
Mast lowered height	2110mm
Length(Without Fork)	2650/2693mm
Width	1225mm
Height	2160/2165mm
Tires	28x9-15/6.50-10-10PR
Wheel base	1700mm
Turning Radius (outside)	2400/2420mm
Service weight	4180/4390kg
Battery Type	Lithium
Battery Capacity	80V/280Ah

CPD30/35



» Off-Road Forklift



RTF-20

Rated capacity	2000kg
Lift height	3000-6000mm
Mast lowered height	2230mm
Length(Without Fork)	3650mm
Width	1500mm
Height	2200mm
Tires	20.5/70-16
Wheel base	2000mm
Turning Radius (outside)	3300mm
Service weight	4050kg
Engine Model	YN490
Rated power	42kw



RTF-30

Rated capacity	3000kg
Lift height	3000-6000mm
Mast lowered height	2450mm
Length(Without Fork)	3700mm
Width	1800mm
Height	2450mm
Tires	20.5/70-16
Wheel base	2250mm
Turning Radius (outside)	3600mm
Service weight	4400kg
Engine Model	YN490
Rated power	42kw



RTF-40

Rated capacity	4000kg
Lift height	3000-6000mm
Mast lowered height	2450mm
Length(Without Fork)	4200mm
Width	1980mm
Height	2600mm
Tires	16/70-20
Wheel base	2400mm
Turning Radius (outside)	3800mm
Service weight	5200kg
Engine Model	YN4100
Rated power	65kw



RTF-50

Rated capacity	5000kg
Lift height	3000-6000mm
Mast lowered height	2500mm
Length(Without Fork)	4400mm
Width	2085mm
Height	2630mm
Tires	16/70-24
Wheel base	2450mm
Turning Radius (outside)	3900mm
Service weight	5820kg
Engine Model	YN4102
Rated power	76kw



HRTF302

Rated capacity	3000kg
Lift height	3000-6000mm
Mast lowered height	2185mm
Length(Without Fork)	2940mm
Width	1550mm
Height	2210mm
Tires	12-16.5/27X10
Wheel base	1850mm
Turning Radius (outside)	2910mm
Service weight	4900kg
Engine Model	Xinchai C490BPG
Rated power	40kw

HRTF304

Rated capacity	3000kg
Lift height	3000-6000mm
Mast lowered height	2185mm
Length(Without Fork)	2940mm
Width	1550mm
Height	2210mm
Tires	12-16.5
Wheel base	1850mm
Turning Radius (outside)	2910mm
Service weight	4900kg
Engine Model	Xinchai C490BPG
Rated power	40kw



Rough Terrain Forklift



H20

Rated loading	2000kg
Dimension	3030x1650x2105mm
Height	3831mm
Ground clearance	260mm
Wheel base	1800mm
Operating weight	4000kg
Engine	KUBOTA/PERKINS/KOHLER
Max speed	20km
Oil tank	65L
Tire	400/70-20



H25

Rated loading	2500kg
Dimension	3030x1650x2105mm
Height	3831mm
Ground clearance	260mm
Wheel base	1800mm
Operating weight	4300kg
Engine	KUBOTA/PERKINS/KOHLER
Max speed	20km
Oil tank	65L
Tire	400/70-20



CPCY20

Rated loading	2000kg
Dimension	3500x2550x3708mm
Height	3000mm
Ground clearance	206mm
Wheel base	1785mm
Operating weight	3200kg
Engine	YUNNEI
Load center distance	565mm
Drive Mean	Four Wheel drive
Max climbing power(%)	30
Tire	12-16.5



CPCY30

Rated loading	3000kg
Dimension	4000x1800x2750mm
Height	3000mm
Ground clearance	270mm
Wheel base	2100mm
Operating weight	4680kg
Engine	YUNNEI
Load center distance	500mm
Full load liftingspeed	380mm/s
Max speed	30km
Tire	12-16.5



H30

Rated loading	3000kg
Dimension	4594x1720x2224mm
Height	4500mm
Ground clearance	280mm
Wheel base	1800mm
Operating weight	5700kg
Engine	CUMMINS/KUBOTA/KOHLER
Max speed	20/35km
Oil tank	65L
Tire	12-16.5



H35

Rated loading	3500kg
Dimension	4594x1720x2224mm
Height	4500mm
Ground clearance	280mm
Wheel base	1800mm
Operating weight	6000kg
Engine	CUMMINS/KUBOTA/KOHLER
Max speed	20/35km
Oil tank	65L
Tire	12-16.5

CPCY40/50

Rated loading	4000/5000kg
Dimension	6000x2080x2950mm
Fuill Height when max lifting	4500mm
Height of the mast	3500mm
Ground clearance	260/300mm
No fork Length	4680mm
Drive Mean	Four Wheel drive
Max speed	35km
Tire	16/90-24

