Ravelli®
il fuoco intelligente

HEAT INPUT POWER	TOTAL HEAT OUTPUT
BTU/hr 10.000 - 50.000	BTU/hr 8.5000 -44.000

RV 100 CLASSIC

330lb - 55 lb Pellet





White
Blanc



Bordeaux
Bordeaux



Parchment
Parchemin



Black
Noir

- Efficiency (based on LHV) 85%
- Rounded cast iron front part
- Cast iron firepot
- Wide view of the flames
- Extractable ash pan
- Top exhaust tube
- Sliding structure for Easy Inspection

Ravelli®
il fuoco intelligente

HEAT INPUT POWER
BTU/hr 10.000- 50.000

TOTAL HEAT OUTPUT
BTU/hr 8.500- 44.000

RV 100 CLASSIC

330lb - 55 lb Pellet

FIREX
CLEAR
INOX
ECO START
TIMER
REMOTE CONTROL
ASH
MAJOLICA
RDS



RAVELLI DYNAMIC SYSTEM
RDS is Ravelli's innovative system for automatically regulating combustion parameters and ensuring maximum efficiency and safety from your stove.

FIREX 600
All Ravelli's products have a combustion chamber made from FIREX 600, a vermiculite based material developed by Ravelli after long and extensive research.

GLASS CLEANING SYSTEM
A supplementary air duct over the door creates an air cushion between the flame and the ceramic glass, to keep the door glass clean for many hours of burning.

ECO-START QUICK IGNITION SYSTEM
The Eco-Start ignition system ensures that the stove lights quickly and safely. By reducing the time for which the ignition element has to operate, the system dramatically extends its life.

TIMER-THERMOSTAT
A timer-thermostat lets you program in two ignition times and two finish times so that you can make optimal daily and weekly use of the stove.

REMOTE CONTROL WITH GRAPHIC DISPLAY
A practical and convenient remote control allows you to adjust temperature and power as required. Moreover, it helps to perform the stove programming laying confortably on the sofa.

CAST MAJOLICA BODY
The attractively shaped stove body is in colourful majolica for a high prestige finish and excellent heat diffusion.

ASH PAN
A functional and easily accessible ash pan collects all the burned out ash.

STAINLESS STEEL HEAT EXCHANGER
A stainless steel heat exchanger means increased fire resistance and reduced wear.

HEAT INPUT	BTU/hr	10,000 – 50,000
HEAT OUTPUT	BTU/hr	8,500 – 44,000
FEED RATE	lb/hr	1.32 – 5.29
EFFICIENCY (based on LHV)	%	87,5
VENTING SIZE	Ø mm	80/3.15
HOPPER CAPACITY	lb	55
BURN TIME	hr	10.4 – 41.7
NET WEIGHT	lb	330

The manufacturer assumes no responsibility for any errors or inaccuracies in the content of this catalog and reserves the right to modify its products at any time and without prior notice, and make changes considered appropriate for either technical or commercial reasons.

www.ravelligroup.it

